



D5406-1 CONNECTOR

NOTES:

- 1) MATERIAL: AISI 304/316 SS SHEET, 16 GAUGE
ANNEALED, 2B FINISH
PER MIL-S-5059
OR AMS 5513 (304)
OR AMS 5524 (316)
OR ASTM A240
OR ASME SA240
REF DART SPEC M304S16GA
- 2) FINISH: POWDER COAT "WHITE" (4.3.5.2) PER DART QSI 005 4.3
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
- 7) WEIGHT: 0.04 lbs
- 8) MASK HOLES PRIOR TO POWDER COAT

RELEASED
2016-11-24
EN 16-674

APPROVED

A	NEW ISSUE		VS	16.05.10
REV.	DESCRIPTION		BY	DATE
DESIGN	VS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA		
DRAWN	VS			
CHECKED	RF	DRAWING NO. D5406		REV. A
MFG. APPR.	JLM			SHEET 1 OF 1
APPROVED	HS	TITLE CONNECTOR		SCALE
DE APPR.	DS			NTS
DATE	16.05.10		<small>COPYRIGHT © 2016 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	